



## EW-IP4060B

With features of simple installation, easy operation, and high performance-cost ratio, This Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises. This product uses the latest PoE technology to troubleshoot the occurrence of any issues in the system making it easier to use. With the help of this technology, your camera now only consumes energy directly from the power supply and doesn't require any mid-way switches. Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas

### Key Features-



- ❖ 1/3" Progressive Scan CMOS
- ❖ 2560×1440@25/30 fps, MJPEG up to 1920×1080@30 fps
- ❖ 3.6 mm Fixed Lenses
- ❖ Color: 0.01 Lux @ (F1.6, 30IRE)
- ❖ H.265, H.265+, H.264, H.264+
- ❖ 120 dB WDR
- ❖ 3D DNR
- ❖ IR Range up to 80 Meter
- ❖ Alarm I/O

### Specification

<b>Camera</b>	Image Sensor:	1/3" Progressive Scan CMOS Image Sensor
	Scanning System:	Progressive
	Min. Illumination:	Color: 0.005 Lux @ (F1.6, 30IRE) B/W: 0.0005 Lux @ (F1.6, 30IRE) 0 Lux (Illuminator On)
	Effective Pixels:	2560(H) x 1440(V)
	Shutter Time:	Auto/Manual 1/3s – 1/100000 sec
	Slow Shutter:	Yes
	P-IRIS	Yes
	DNR:	3D DNR
	Max. Image Resolution:	4 Mega Pixel (2560x1440) @ 20/25fps
	Day& Night:	IR Cut Filter.
	WDR:	120dB, DWDR

	<table border="1"> <tr> <td>BLC/AGC/SI/AWB:</td> <td>Auto/Manual</td> </tr> <tr> <td>Gain Control:</td> <td>Auto/Manual</td> </tr> <tr> <td>NR:</td> <td>3D DNR</td> </tr> <tr> <td>S/N Ratio:</td> <td>&gt;56db</td> </tr> <tr> <td>White Balance:</td> <td>Auto/Manual/Natural/Street Lamp/Outdoor/Regional</td> </tr> <tr> <td>Angle Adjustment:</td> <td>Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°</td> </tr> <tr> <td>Back Light Compensation:</td> <td>BLC/HLC/WDR (120DB)</td> </tr> </table>	BLC/AGC/SI/AWB:	Auto/Manual	Gain Control:	Auto/Manual	NR:	3D DNR	S/N Ratio:	>56db	White Balance:	Auto/Manual/Natural/Street Lamp/Outdoor/Regional	Angle Adjustment:	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°	Back Light Compensation:	BLC/HLC/WDR (120DB)				
BLC/AGC/SI/AWB:	Auto/Manual																		
Gain Control:	Auto/Manual																		
NR:	3D DNR																		
S/N Ratio:	>56db																		
White Balance:	Auto/Manual/Natural/Street Lamp/Outdoor/Regional																		
Angle Adjustment:	Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°																		
Back Light Compensation:	BLC/HLC/WDR (120DB)																		
<b>Camera Lens</b>	<table border="1"> <tr> <td>Focal Length:</td> <td>3.6MM</td> </tr> <tr> <td>Lens Type:</td> <td>Fixed Focal</td> </tr> <tr> <td>Mount Type:</td> <td>M12</td> </tr> <tr> <td>Max Aperture:</td> <td>F2.0</td> </tr> <tr> <td>IRIS Type:</td> <td>Fixed IRIS</td> </tr> <tr> <td>Angle of View:</td> <td>3.6mm: H: 76°, V: 40°, D: 92°</td> </tr> <tr> <td>ICR:</td> <td>Auto (ICR)/Color/B/W</td> </tr> <tr> <td>Close Focus Distance:</td> <td>3.6mm-1.4m</td> </tr> <tr> <td>Digital Zoom:</td> <td>16X</td> </tr> </table>	Focal Length:	3.6MM	Lens Type:	Fixed Focal	Mount Type:	M12	Max Aperture:	F2.0	IRIS Type:	Fixed IRIS	Angle of View:	3.6mm: H: 76°, V: 40°, D: 92°	ICR:	Auto (ICR)/Color/B/W	Close Focus Distance:	3.6mm-1.4m	Digital Zoom:	16X
Focal Length:	3.6MM																		
Lens Type:	Fixed Focal																		
Mount Type:	M12																		
Max Aperture:	F2.0																		
IRIS Type:	Fixed IRIS																		
Angle of View:	3.6mm: H: 76°, V: 40°, D: 92°																		
ICR:	Auto (ICR)/Color/B/W																		
Close Focus Distance:	3.6mm-1.4m																		
Digital Zoom:	16X																		
<b>IR</b>	<table border="1"> <tr> <td>IR Range:</td> <td>Up to 80 Meter</td> </tr> <tr> <td>Wavelength:</td> <td>850nm</td> </tr> </table>	IR Range:	Up to 80 Meter	Wavelength:	850nm														
IR Range:	Up to 80 Meter																		
Wavelength:	850nm																		
<b>Sharpness</b>	<table border="1"> <tr> <td>HLC:</td> <td>50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)</td> </tr> <tr> <td>BLC:</td> <td>Support</td> </tr> <tr> <td>OSD:</td> <td>8 OSD</td> </tr> <tr> <td>ROI:</td> <td>3 Area</td> </tr> <tr> <td>Defog:</td> <td>Digital Defog</td> </tr> </table>	HLC:	50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)	BLC:	Support	OSD:	8 OSD	ROI:	3 Area	Defog:	Digital Defog								
HLC:	50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)																		
BLC:	Support																		
OSD:	8 OSD																		
ROI:	3 Area																		
Defog:	Digital Defog																		
<b>Compression</b>	<table border="1"> <tr> <td>Video Compression:</td> <td>Main Stream: H.265/H.264/H.265+/H.264+ Sub Stream/ Third Stream/Fourth Stream/Fifth Stream/Custom Stream: H.265/H.264/MJPEG</td> </tr> <tr> <td>H.265 Code Type:</td> <td>Baseline Profile/Main Profile/High Profile</td> </tr> <tr> <td>Bit Rate:</td> <td>CBR/VBR</td> </tr> <tr> <td>Video Bit Rate:</td> <td>32 Kbps–6 Mbps</td> </tr> <tr> <td>Audio Compression:</td> <td>G.711a/G.711Mu/G.722.1/G.726/MP2L2/PCM</td> </tr> <tr> <td>Audio Bit Rate:</td> <td>64Kbps(G.711)/16Kbps(G.722.1)/16Kbps (G.726)/ 32-192Kbps (MP2L2)/32Kbps (PCM)</td> </tr> </table>	Video Compression:	Main Stream: H.265/H.264/H.265+/H.264+ Sub Stream/ Third Stream/Fourth Stream/Fifth Stream/Custom Stream: H.265/H.264/MJPEG	H.265 Code Type:	Baseline Profile/Main Profile/High Profile	Bit Rate:	CBR/VBR	Video Bit Rate:	32 Kbps–6 Mbps	Audio Compression:	G.711a/G.711Mu/G.722.1/G.726/MP2L2/PCM	Audio Bit Rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps (G.726)/ 32-192Kbps (MP2L2)/32Kbps (PCM)						
Video Compression:	Main Stream: H.265/H.264/H.265+/H.264+ Sub Stream/ Third Stream/Fourth Stream/Fifth Stream/Custom Stream: H.265/H.264/MJPEG																		
H.265 Code Type:	Baseline Profile/Main Profile/High Profile																		
Bit Rate:	CBR/VBR																		
Video Bit Rate:	32 Kbps–6 Mbps																		
Audio Compression:	G.711a/G.711Mu/G.722.1/G.726/MP2L2/PCM																		
Audio Bit Rate:	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps (G.726)/ 32-192Kbps (MP2L2)/32Kbps (PCM)																		

<b>Image</b>	Max. Resolution:	2560x1440
	Video Streaming:	Main Stream: 2560 × 1440@ (1–25/30 fps) Sub Stream: 704 × 576@ (1–25/30 fps)/704 × 480@ (1–30 fps)
	Resolution:	4MP (2560 × 1440); 3MP (2304 × 1296); 2MP (1920 × 1080); 1.3MP (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
	Image Enhancement:	BLC, HLC, 3D DNR, Defog, EIS, ROI, AWB, AGC
	Image Setting:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, Hue, Adjustable by Client Software or Web Browser
	Image Rotation:	0°/180°
	Target Cropping:	Yes
	SVC:	H.264 and H.265 Encoding
<b>Audio</b>	In Built Audio:	Yes
	Audio Support:	Yes
	Environmental Noise Filtering:	Yes
	Audio Sampling Rate:	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
<b>Network</b>	Abnormal Detection:	Motion Detection, Video Tampering, Network Disconnect, IP Address Conflict, Illegal Login, HDD Full, HDD Error
	Edge Analytics:	Intrusion, tripwire/ line crossing/ vehicle and human
	Alarm Event:	No SD card, SD card full, SD card error, network disconnection, illegal aces, Moton detection, video tampering, tripwire, intrusion, SMD, voltage detection, security exception
	Protocols:	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour, ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec;
	Simultaneous View:	Up To 20 Channels
	Users:	20
	Privacy Masking:	3 Areas
	Motion Detection:	Off/On 3 Areas
	Mobile:	iPhone, iPad, Android
	Cyber Security:	Configuration encryption, Trusted execution, Digest, Security logs, WSSE, Account lockout, syslog, Video encryption,802.1x,IP/MAC filtering, HTTPS, Trusted upgrade, Trusted boot, Gen- eration and importing of X.509 certification
	Compatible Integration:	ONVIF (Profile S/Profile G/Profile T), CGI
SDK and API:	Yes	

	<table border="1"> <tr> <td>Mirror:</td> <td>Yes</td> </tr> <tr> <td>Encrypted Data Transmission:</td> <td>HTTPS (SSL/TSL)</td> </tr> <tr> <td>Web Browser:</td> <td>IE8+, Chrome41.0-44, Firefox30.0-51, Safari8.0-11</td> </tr> <tr> <td>General Function:</td> <td>One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter</td> </tr> </table>	Mirror:	Yes	Encrypted Data Transmission:	HTTPS (SSL/TSL)	Web Browser:	IE8+, Chrome41.0-44, Firefox30.0-51, Safari8.0-11	General Function:	One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter										
Mirror:	Yes																		
Encrypted Data Transmission:	HTTPS (SSL/TSL)																		
Web Browser:	IE8+, Chrome41.0-44, Firefox30.0-51, Safari8.0-11																		
General Function:	One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter																		
<b>Interface</b>	<table border="1"> <tr> <td>Communication Interface:</td> <td>1 RJ45 10M / 100M Ethernet Interface Port</td> </tr> <tr> <td>Audio:</td> <td>1 Input, 1 Output, Mono Sound</td> </tr> <tr> <td>Alarm:</td> <td>1 Input, 1 Output</td> </tr> <tr> <td>Video Output:</td> <td>1Vp-p composite output (75 Ω/ CVBS)</td> </tr> <tr> <td>On Board Storage:</td> <td>Support SD/Micro SD Card Up to 256GB/NAS</td> </tr> <tr> <td>Reset Button:</td> <td>Yes</td> </tr> </table>	Communication Interface:	1 RJ45 10M / 100M Ethernet Interface Port	Audio:	1 Input, 1 Output, Mono Sound	Alarm:	1 Input, 1 Output	Video Output:	1Vp-p composite output (75 Ω/ CVBS)	On Board Storage:	Support SD/Micro SD Card Up to 256GB/NAS	Reset Button:	Yes						
Communication Interface:	1 RJ45 10M / 100M Ethernet Interface Port																		
Audio:	1 Input, 1 Output, Mono Sound																		
Alarm:	1 Input, 1 Output																		
Video Output:	1Vp-p composite output (75 Ω/ CVBS)																		
On Board Storage:	Support SD/Micro SD Card Up to 256GB/NAS																		
Reset Button:	Yes																		
<b>Smart Features</b>	<table border="1"> <tr> <td>Behavior Analysis:</td> <td>Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal Detection</td> </tr> <tr> <td>Exception Detection:</td> <td>Scene Change Detection, Defocus Detection</td> </tr> <tr> <td>Statistics:</td> <td>Counting</td> </tr> <tr> <td>Face Detection:</td> <td>Yes</td> </tr> <tr> <td>Smart Detection:</td> <td>Tripwire, Intrusion</td> </tr> <tr> <td>Region of Interest:</td> <td>Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking</td> </tr> </table>	Behavior Analysis:	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal Detection	Exception Detection:	Scene Change Detection, Defocus Detection	Statistics:	Counting	Face Detection:	Yes	Smart Detection:	Tripwire, Intrusion	Region of Interest:	Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking						
Behavior Analysis:	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal Detection																		
Exception Detection:	Scene Change Detection, Defocus Detection																		
Statistics:	Counting																		
Face Detection:	Yes																		
Smart Detection:	Tripwire, Intrusion																		
Region of Interest:	Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking																		
<b>General</b>	<table border="1"> <tr> <td>General Function:</td> <td>Anti-flicker, Heartbeat, Mirror, Password Protection, Privacy Masks, Watermark, IP Address Filter, Tampering Alarm, Access Police, ARP Protection, RTSP Authentication, User Authentication</td> </tr> <tr> <td>Operating Conditions:</td> <td>-40 °C ~ 60 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)</td> </tr> <tr> <td>Power Supply:</td> <td>PoE (IEEE802.3af, 42.5V TO 57V), 0.5A TO 0.3A, MAX 18w</td> </tr> <tr> <td>Power Consumption:</td> <td>Basic: 1.4 W (12 VDC); 2.1 W (PoE) Max. (ICR switch + IR intensity): 3.0 W (12 VDC); 4.2 W (PoE)</td> </tr> <tr> <td>Casing:</td> <td>Metal/Plastic</td> </tr> <tr> <td>Weather Proof:</td> <td>IP 67 IK10</td> </tr> <tr> <td>Weight:</td> <td>0.450g</td> </tr> <tr> <td>Certification:</td> <td>BIS, CE, FC, ROHS, GDPR, ISO</td> </tr> <tr> <td>Country of Origin:</td> <td>India</td> </tr> </table>	General Function:	Anti-flicker, Heartbeat, Mirror, Password Protection, Privacy Masks, Watermark, IP Address Filter, Tampering Alarm, Access Police, ARP Protection, RTSP Authentication, User Authentication	Operating Conditions:	-40 °C ~ 60 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)	Power Supply:	PoE (IEEE802.3af, 42.5V TO 57V), 0.5A TO 0.3A, MAX 18w	Power Consumption:	Basic: 1.4 W (12 VDC); 2.1 W (PoE) Max. (ICR switch + IR intensity): 3.0 W (12 VDC); 4.2 W (PoE)	Casing:	Metal/Plastic	Weather Proof:	IP 67 IK10	Weight:	0.450g	Certification:	BIS, CE, FC, ROHS, GDPR, ISO	Country of Origin:	India
General Function:	Anti-flicker, Heartbeat, Mirror, Password Protection, Privacy Masks, Watermark, IP Address Filter, Tampering Alarm, Access Police, ARP Protection, RTSP Authentication, User Authentication																		
Operating Conditions:	-40 °C ~ 60 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)																		
Power Supply:	PoE (IEEE802.3af, 42.5V TO 57V), 0.5A TO 0.3A, MAX 18w																		
Power Consumption:	Basic: 1.4 W (12 VDC); 2.1 W (PoE) Max. (ICR switch + IR intensity): 3.0 W (12 VDC); 4.2 W (PoE)																		
Casing:	Metal/Plastic																		
Weather Proof:	IP 67 IK10																		
Weight:	0.450g																		
Certification:	BIS, CE, FC, ROHS, GDPR, ISO																		
Country of Origin:	India																		