



EW-S4PGF2

Specification:-

Network Interface:	4 10/100/1000Mbps PoE RJ45 port (port 1 port 4) 2 1000Mbps SFP Slots
Standard Network Protocols:	IEEE802.3 10BASE-T, IEEE 802.3u 100BASE—TX, ANSI/IEEE 802.3 NWay Auto-Negotiation, IEEE802.3x Flow Control, IEEE 802.3af/at standard
Forwarding Method:	Store-and-Forward
Flow Control:	Back-Pressure Flow Control in IEEE 802.3x Full Duplex
MAC address Table:	1K QoS
Switching Capacity:	1.2 GBPS
Packet Forwarding Rate:	10M:14,800pps 100M: 148,800pps
Forwarding Mode:	Store-and-forward switching
Packet Buffer Memory:	4K
PoE Ports:	1 To 4
Jumbo Frame:	10240 Bytes
PoE Power Budget:	38W
VLAN	Supports up to 4K VLANs Simultaneously (out of 4K VLAN IDs) Port/MAC/Protocol -based VLAN Management VLAN configuration
Operating Temperature:	0 °C to 40 °C
Storage Temperature:	-40 ° ~ 70 ° C
Storage Humidity:	5% to 95% RH Non-Condensing
Power Input:	48V DC, 0.8 A Reverse Connection Protection
Certification:	CE, FCC, ROHS, ISO