

eWit



eWit EW-IP20150Z 2 MP 30x Network IP PTZ Speed Dome adopts 1/2.8" progressive scan CMOS chip. With the 30x optical zoom lens, the camera offers more details over expansive areas. This series of cameras can be widely used for wide ranges of high-definition, such as the rivers, roads, railways, airports, squares, parks, scenic spots, and venues, etc.



EW-IP20150Z

Key Features: -

- 1/2.8" 2MP PS CMOS Image sensor (0.9071 centimeters)
- Max. 50/60fps@1080P
- Powerful 30x Optical and 16x Digital zoom
- WDR (120dB), 3D DNR, Day/Night (ICR), EIS, Defog, ROI, BLC, HLC
- Support Starlight Technology • Up to 300 presets, auto scan, 8 tour, 5 pattern, auto pan
- IR Range of 150 Meter, IP66, Support PoE+
- Max 400° /s pan speed, 360° endless pan rotation
- Built-in 2/1 alarm in/out

Specification

Camera	Image Sensor:	1/2.8" Progressive Scan CMOS Sensor (0.9071 CM)
	Effective Pixels:	1920(H) x 1080(V)
	Resolution:	2 MP
	Minimum Illumination:	Color: 0.005 Lux (F 1.5, AGC On) B/W: 0.0005 Lux (F1.5, AGC On) 0 Lux @ F1.6 (IR On)
	White Balance:	Auto/Manual/ATW (Auto-Tracking White Balance)/ Indoor/Outdoor/Fluorescent Lamp/Sodium Lamp
	Gain Control:	Auto/Manual
	Shutter Time:	50Hz: 1/1s to 1/100,000s 60Hz: 1/1s to 1/100,000s
	Auto Exposure:	Automatic Level Control/Electronic Level Control

	<table border="1"> <tr> <td>Signal Process:</td> <td>Digital Signal Process</td> </tr> <tr> <td>Privacy Mask:</td> <td>24 Programmable Privacy Masks, Mask Color Configurable</td> </tr> <tr> <td>Focus Mode:</td> <td>Auto/Manual</td> </tr> <tr> <td>WDR:</td> <td>140 dB WDR</td> </tr> <tr> <td>DNR:</td> <td>3D DNR</td> </tr> <tr> <td>AGC Control:</td> <td>Auto/Manual</td> </tr> <tr> <td>IR Intensity:</td> <td>Automatic</td> </tr> <tr> <td>PTZ Controls:</td> <td>Yes</td> </tr> <tr> <td>S/N Ratio:</td> <td>>55db</td> </tr> <tr> <td>Back Light Compensation:</td> <td>BLC/HLC/WDR (120db)</td> </tr> </table>	Signal Process:	Digital Signal Process	Privacy Mask:	24 Programmable Privacy Masks, Mask Color Configurable	Focus Mode:	Auto/Manual	WDR:	140 dB WDR	DNR:	3D DNR	AGC Control:	Auto/Manual	IR Intensity:	Automatic	PTZ Controls:	Yes	S/N Ratio:	>55db	Back Light Compensation:	BLC/HLC/WDR (120db)				
Signal Process:	Digital Signal Process																								
Privacy Mask:	24 Programmable Privacy Masks, Mask Color Configurable																								
Focus Mode:	Auto/Manual																								
WDR:	140 dB WDR																								
DNR:	3D DNR																								
AGC Control:	Auto/Manual																								
IR Intensity:	Automatic																								
PTZ Controls:	Yes																								
S/N Ratio:	>55db																								
Back Light Compensation:	BLC/HLC/WDR (120db)																								
Lens	<table border="1"> <tr> <td>Focal Length:</td> <td>4.8~120MM</td> </tr> <tr> <td>Digital Zoom:</td> <td>16X</td> </tr> <tr> <td>Optical Zoom:</td> <td>30X</td> </tr> <tr> <td>Aperture Range:</td> <td>F1.6~4.4</td> </tr> <tr> <td>Zoom Speed:</td> <td>3.6s Approx</td> </tr> <tr> <td>DORI Distance:</td> <td>D: 1613M, O: 646M, R: 323M, I: 161M</td> </tr> <tr> <td>Angel of View:</td> <td>H: 62.8°~2.6°</td> </tr> <tr> <td>Focus Control:</td> <td>Auto/Manual</td> </tr> <tr> <td>Close Focus Distance:</td> <td>100~1000mm (Wide-Tele)</td> </tr> </table>	Focal Length:	4.8~120MM	Digital Zoom:	16X	Optical Zoom:	30X	Aperture Range:	F1.6~4.4	Zoom Speed:	3.6s Approx	DORI Distance:	D: 1613M, O: 646M, R: 323M, I: 161M	Angel of View:	H: 62.8°~2.6°	Focus Control:	Auto/Manual	Close Focus Distance:	100~1000mm (Wide-Tele)						
Focal Length:	4.8~120MM																								
Digital Zoom:	16X																								
Optical Zoom:	30X																								
Aperture Range:	F1.6~4.4																								
Zoom Speed:	3.6s Approx																								
DORI Distance:	D: 1613M, O: 646M, R: 323M, I: 161M																								
Angel of View:	H: 62.8°~2.6°																								
Focus Control:	Auto/Manual																								
Close Focus Distance:	100~1000mm (Wide-Tele)																								
IR	<table border="1"> <tr> <td>IR Range:</td> <td>150 Meter</td> </tr> <tr> <td>Smart IR:</td> <td>Yes</td> </tr> </table>	IR Range:	150 Meter	Smart IR:	Yes																				
IR Range:	150 Meter																								
Smart IR:	Yes																								
PTZ	<table border="1"> <tr> <td>Pan Range:</td> <td>0~360° Endless</td> </tr> <tr> <td>Tilt Range:</td> <td>Auto Flip from -15° to 90°</td> </tr> <tr> <td>PAN Speed:</td> <td>0.1°/s to 300°/s Preset Speed: 120°/s</td> </tr> <tr> <td>Tilt Speed:</td> <td>0.1°/s to 180°/s Preset Speed: 200°/s</td> </tr> <tr> <td>Presets:</td> <td>300</td> </tr> <tr> <td>Preset Speed:</td> <td>Pan: 400° /s; Tilt: 300° /s</td> </tr> <tr> <td>Proportional Zoom:</td> <td>Available</td> </tr> <tr> <td>Power of Memory:</td> <td>Yes</td> </tr> <tr> <td>Pattern Scan:</td> <td>4 Pattern Scans, Record Time Over 10 Minutes for Each Scan</td> </tr> <tr> <td>Park Action:</td> <td>Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan</td> </tr> <tr> <td>Patrol Scan:</td> <td>8 Patrols, up to 32 Presets for Each Patrol</td> </tr> <tr> <td>3D Positioning:</td> <td>Yes</td> </tr> </table>	Pan Range:	0~360° Endless	Tilt Range:	Auto Flip from -15° to 90°	PAN Speed:	0.1°/s to 300°/s Preset Speed: 120°/s	Tilt Speed:	0.1°/s to 180°/s Preset Speed: 200°/s	Presets:	300	Preset Speed:	Pan: 400° /s; Tilt: 300° /s	Proportional Zoom:	Available	Power of Memory:	Yes	Pattern Scan:	4 Pattern Scans, Record Time Over 10 Minutes for Each Scan	Park Action:	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan	Patrol Scan:	8 Patrols, up to 32 Presets for Each Patrol	3D Positioning:	Yes
Pan Range:	0~360° Endless																								
Tilt Range:	Auto Flip from -15° to 90°																								
PAN Speed:	0.1°/s to 300°/s Preset Speed: 120°/s																								
Tilt Speed:	0.1°/s to 180°/s Preset Speed: 200°/s																								
Presets:	300																								
Preset Speed:	Pan: 400° /s; Tilt: 300° /s																								
Proportional Zoom:	Available																								
Power of Memory:	Yes																								
Pattern Scan:	4 Pattern Scans, Record Time Over 10 Minutes for Each Scan																								
Park Action:	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan																								
Patrol Scan:	8 Patrols, up to 32 Presets for Each Patrol																								
3D Positioning:	Yes																								

	<table border="1"> <tr> <td>PTZ Position Display:</td> <td>Yes</td> </tr> <tr> <td>Preset Freezing:</td> <td>Yes</td> </tr> <tr> <td>Scheduled Task:</td> <td>Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output</td> </tr> </table>	PTZ Position Display:	Yes	Preset Freezing:	Yes	Scheduled Task:	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output														
PTZ Position Display:	Yes																				
Preset Freezing:	Yes																				
Scheduled Task:	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output																				
Compression Standard	<table border="1"> <tr> <td>Video Compression:</td> <td>Main stream: 1080P/720P/1.3M (1 ~ 50/60fps), Sub stream1: D1/CIF (1 ~ 25/30fps), Sub stream2: 1080P/1.3M/720P/D1/ CIF (1 ~ 25/30fps)</td> </tr> <tr> <td>H.264 Type:</td> <td>Baseline Profile/Main Profile/High Profile</td> </tr> <tr> <td>H.264+:</td> <td>Yes</td> </tr> <tr> <td>H.265 Type:</td> <td>Baseline Profile/Main Profile/High Profile</td> </tr> <tr> <td>H.265+:</td> <td>Yes</td> </tr> <tr> <td>Bit Rate Control:</td> <td>CBR/VBR</td> </tr> <tr> <td>Video Bit Rate:</td> <td>H.265/H.264: 448 K to 8192 Kbps</td> </tr> <tr> <td>Audio Compression:</td> <td>G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM</td> </tr> <tr> <td>Audio Bit Rate:</td> <td>G.711alaw/G.711ulaw: 64 Kbps G.722.1/G.726: 16 Kbps MP212/PCM: 32 Kbps to 160 Kbps</td> </tr> <tr> <td>SVC:</td> <td>Yes</td> </tr> </table>	Video Compression:	Main stream: 1080P/720P/1.3M (1 ~ 50/60fps), Sub stream1: D1/CIF (1 ~ 25/30fps), Sub stream2: 1080P/1.3M/720P/D1/ CIF (1 ~ 25/30fps)	H.264 Type:	Baseline Profile/Main Profile/High Profile	H.264+:	Yes	H.265 Type:	Baseline Profile/Main Profile/High Profile	H.265+:	Yes	Bit Rate Control:	CBR/VBR	Video Bit Rate:	H.265/H.264: 448 K to 8192 Kbps	Audio Compression:	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM	Audio Bit Rate:	G.711alaw/G.711ulaw: 64 Kbps G.722.1/G.726: 16 Kbps MP212/PCM: 32 Kbps to 160 Kbps	SVC:	Yes
Video Compression:	Main stream: 1080P/720P/1.3M (1 ~ 50/60fps), Sub stream1: D1/CIF (1 ~ 25/30fps), Sub stream2: 1080P/1.3M/720P/D1/ CIF (1 ~ 25/30fps)																				
H.264 Type:	Baseline Profile/Main Profile/High Profile																				
H.264+:	Yes																				
H.265 Type:	Baseline Profile/Main Profile/High Profile																				
H.265+:	Yes																				
Bit Rate Control:	CBR/VBR																				
Video Bit Rate:	H.265/H.264: 448 K to 8192 Kbps																				
Audio Compression:	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM																				
Audio Bit Rate:	G.711alaw/G.711ulaw: 64 Kbps G.722.1/G.726: 16 Kbps MP212/PCM: 32 Kbps to 160 Kbps																				
SVC:	Yes																				
Smart Feature	<table border="1"> <tr> <td>Basic Event:</td> <td>Motion Detection, Video Tampering Detection, Exception</td> </tr> <tr> <td>Smart Event:</td> <td>Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection</td> </tr> <tr> <td>Smart Record:</td> <td>ANR</td> </tr> <tr> <td>ROI/Defog/AWB/BLC/HLC:</td> <td>Support</td> </tr> <tr> <td>Auto-Tracking:</td> <td>Yes</td> </tr> <tr> <td>Special Feature:</td> <td>Defog, IR Range up to 150m, Up to 300 Presets, 5 Pattern, 8 Tour, Auto Pan, Auto Scan</td> </tr> </table>	Basic Event:	Motion Detection, Video Tampering Detection, Exception	Smart Event:	Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection	Smart Record:	ANR	ROI/Defog/AWB/BLC/HLC:	Support	Auto-Tracking:	Yes	Special Feature:	Defog, IR Range up to 150m, Up to 300 Presets, 5 Pattern, 8 Tour, Auto Pan, Auto Scan								
Basic Event:	Motion Detection, Video Tampering Detection, Exception																				
Smart Event:	Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection																				
Smart Record:	ANR																				
ROI/Defog/AWB/BLC/HLC:	Support																				
Auto-Tracking:	Yes																				
Special Feature:	Defog, IR Range up to 150m, Up to 300 Presets, 5 Pattern, 8 Tour, Auto Pan, Auto Scan																				
Image	<table border="1"> <tr> <td>Max. Resolution:</td> <td>2560 × 1440</td> </tr> <tr> <td>Main Stream:</td> <td>30fps@ (1920x1080, 1280x960, 1280x720, 704x576)</td> </tr> <tr> <td>Sub-Stream:</td> <td>30fps@ (704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)</td> </tr> <tr> <td>Third Stream:</td> <td>50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)</td> </tr> <tr> <td>Image Enhancement:</td> <td>HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus</td> </tr> </table>	Max. Resolution:	2560 × 1440	Main Stream:	30fps@ (1920x1080, 1280x960, 1280x720, 704x576)	Sub-Stream:	30fps@ (704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	Third Stream:	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)	Image Enhancement:	HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus										
Max. Resolution:	2560 × 1440																				
Main Stream:	30fps@ (1920x1080, 1280x960, 1280x720, 704x576)																				
Sub-Stream:	30fps@ (704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)																				
Third Stream:	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)																				
Image Enhancement:	HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus																				

Network	Alarm Linkage:	Alarm actions, such as Preset, Patrol Scan, Pattern Scan, Trigger Recording, Trigger Alarm Output, Notify Surveillance Centre, Upload to FTP/Memory Card/NAS, Send Email, etc.
	API:	ONVIF (Profile S, Profile G, Profile T), ISAPI, SDK
	Protocols:	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
	Simultaneous Live View:	Up to 20 channels
	User/Host:	Up to 32 users 3 levels: Administrator, Operator and User
	Security Measures:	User Authentication (ID and PW), Host Authentication (MAC Address); HTTPS Encryption; IEEE 802.1x Port-Based Network Access Control; IP Address Filtering
	Web Browser:	IE 8 to 11, Chrome 31.0+, Firefox 30.0+
Interface	Network Interface:	1 RJ45 10 M/100 M Ethernet, Hi-PoE
	Audio Input/ Output:	1-Ch Audio Input, 2 to 2.4 V[p-p], 1 K Ω \pm 10% 1-Ch Audio Output, Line Level, Impedance: 600 Ω
	Alarm Input/ Output:	2-Ch Alarm Input/1-ch Alarm Output
	On Board Storage:	Support Micro SD Card Up to 256 GB
General	Language:	English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil)
	Power:	24 VAC, 2.2 A, 50/60 Hz and Hi-PoE, 42.5 to 57 VDC, 1.41 A Max.: 30 W, including max. 10W for IR
	Working Temperature:	-30°C to 65°C (-22°F to 149°F)
	Working Humidity:	\leq 90%
	Protection Level:	IP66
	Material:	ADC 12, PC+10% GF
	Weight:	3.5 Kg
	Certificate:	ISO, CE, FC, ROHS
Country of Origin:	India	